



Customers ZIP Past The Drive-Thru Lane With Contactless Payments

ViVOpay DT speeds up the drive-thru lane with fast and convenient contactless payments.

The ViVOpay DT is a ruggedized contactless reader that enables contactless payments at drive-thru locations. Its flexible design allows mounting to walls, metal poles and sign boards at areas conveniently located near the drive-thru payment window.

ViVOpay DT enables contactless payments at new and existing Point of Sale (POS) and Electronic Cash Register (ECR) systems by allowing consumers to simply tap their contactless cards at the ViVOpay DT-enabled drive-thru terminal to complete a payment transaction. During the contactless payment trials the most significant time savings was realized in the drive-thru environment, where transaction time were reduced by up to 18 seconds.*

ViVOpay DT is compatible with MasterCard® PayPass™, ExpressPay from American Express®, Visa® Contactless and Discover Contactless payment programs. Using the ViVOpay DT in conjunction with the ViVOplatform™, Quick Service Restaurants (QSRs) can enhance customer loyalty and issue contactless gift cards leading to increased business. Quick Service Restaurants (QSR's) can implement programs with e-coupons, gift and loyalty programs from the countertop to the drive-thru lane.



Benefits

- **Speed and convenience:** Cardholders simply tap their contactless cards to make a payment.
- **High Durability:** Designed for indoor and outdoor use in extreme weather conditions.
- **Low cost:** Costs less than a typical new POS terminal with minimal changes to the existing cash register system.
- **Flexibility:** Side, top, and bottom mounting configurations to fit most drive-thru installations and surface types such as metal and brick.



ViVOpay DT's side, top, and bottom mounting configurations to fit most drive-thru installations and surface types such as metal and brick

(*) *Results of the PayPass Orlando trial verify that the most significant time savings have been recognized in the drive-thru environment which shaved between 12-18 seconds off the purchase time as compared to cash.* - MasterCard International



Features

- **Contactless (RF) technology:** Accepts transactions from consumers using ISO/IEC 14443 Type A and B, and Mifare cards and key fobs.
- **Durability:** Rugged and durable, the reader antenna is enclosed to protect electronic components from harsh weather conditions.
- **Compatibility:** Works with a full range of POS devices for drive-thru, vending machines, kiosks and others.
- **Flexible design:** Easy installation: Easy installation next to the drive-thru window or near the menu board. Includes mounting bracket with security lock and 25 ft. serial connection.
- **Programmable software capability:** Complete upgrade/update capabilities. Merchants can add new functionalities and applications anytime.
- **Value-added services:** ViVOplatform enables e-coupons and gift and loyalty cards and can be customized to existing programs.
- **User friendly interface:** Equipped with LEDs and sound to attract cardholder attention. Provides an interactive and intuitive payment process.
- **Intellectual property:** Protected by several patent-pending applications to ensure high system security.

* ViVOTech, ViVOpay, ViVOpay DT and ViVOplatform are trademarks or registered trademarks of ViVOTech Corporation. All other trademarks or brand names are the properties of their respective holders. Features and specifications are subject to change without notice.



ViVOpay DT's rugged and durable construction offers weather-tight protection for electronic components from harsh weather conditions.

Specifications

Hardware

Serial Port: RS-232 serial interface for connection to an ECR or POS terminal.

Standards

Contactless Interface: 13.56 MHz

Supported Formats: Mifare®
ISO14443 Type A,
ISO14443 Type B, and
ISO15693

Optional Applications

ViVOWallet: Multiple card functionality (e.g. stored value, pre-paid, loyalty, gift, etc.)

ViVOplatform: E-coupon, gift card, and loyalty hosted software

Environmental - Standard

Operating Temperature: -10° to 150° F (-23° to 65° C)

Storage Temperature: -10° to 150° F (-23° to 65° C)

Operating Humidity: 5% to 95%, non-condensing

Rain Tight for outdoor use

Environmental - Extreme Low Temperature

Operating Temperature: -40° to 131° F (-40° to 55° C)

Storage Temperature: -40° to 131° F (-40° to 55° C)

Operating Humidity: 5% to 95%, non-condensing

Rain Tight for outdoor use

Power Requirement

Voltage: 9 VDC

Physical

Physical Dimensions: 165mm (H) x 164mm (W) x 100mm (D)

United States

ViVOTech Corporate Headquarters

451 El Camino Real
Santa Clara, CA 95050
Phone: (408) 248-7001
Fax: (408) 248-7002

International Locations

ASIA Singapore

67 Ubi Avenue 1, #06-02
StarHub Green, North Wing
Singapore 408942
Phone: +65 6634 8289
Fax: +65 6634 8283

EUROPE United Kingdom

38 Petersham Drive, Appleton
Warrington, WA4 5QF,
United Kingdom,
Phone: +44 (0) 1925 269550



www.vivotech.com
sales@vivotech.com